

Mobil™

MOBILGRIND™ 24


HONING/GRINDING OIL

VOC/g/L - 60



DANGER

May be fatal if swallowed and enters airways. Causes skin irritation. Harmful if inhaled. Avoid breathing mist / vapours. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. If SWALLOWED: Immediately call a POISON CENTER or doctor/physician. If ON SKIN: Wash with plenty of soap and water. If INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage. Store locked up. Dispose of contents and container in accordance with local regulations.



NEW JERSEY RIGHT TO KNOW INGREDIENT DESCRIPTION

CAS NUMBER


PETROLEUM OIL (LUBRICANT)
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE

54742-48-7

FOR SHIPMENTS OUTSIDE OF THE U.S. IMO AND ICAO/ATA HAZARD IDENTIFICATION
Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID H.O.S. DISTILLATES (OIL MIDDLE
DISTILLATES)
Class: 9, MARINE POLLUTANT
I.D. No: UN3082 PGII

Made in the USA from domestic and/or imported components.

© 2021 ExxonMobil. All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.



EMPTY CONTAINER WARNING

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SPILL CONTROL

Eliminate all ignition sources. Ventilate confined spaces. Recover free product. Add sand, earth, or other suitable absorbent material to spill area, and keep spilled product out of sewers and water courses. Advise authorities if product cannot be contained. Conform with applicable governmental regulations.

ExxonMobil Oil Corporation
22777 Springwoods Village Parkway
Spring, TX 77389

Visit us at mobil.com

Refer to product Safety Data Sheet (SDS) for further safety and health information.
For product information call 1-800-662-4525
For emergencies call 1-609-737-4411.

D.O.T. Hazard Identification

Name NOT APPLICABLE

Class NOT APPLICABLE

I.D. No. NOT APPLICABLE

AMR121134EMUSF-V5



23

M5942-1B

PACKAGED BY	PRODUCT CODE	BATCH NUMBER	NET WEIGHT / VOLUME
10224B12A	121134	70481407	55 USG/208.2 L