

**ISO 9001
REGISTERED**



590 South Paddock Pontiac, MI 48341
Ph: 248-333-1333 Fax: 248-333-1426

PRODUCT DATA SHEET

Product:	EASTLUBE 3340
NLGI Grade:	1.5
Thickener Type:	Benetone
Color:	White to Light Tan
Texture:	Smooth
Fillers:	Zinc Oxide
Application:	Replaces former Eastern product MS-3340

<u>TEST</u>	<u>METHOD</u>	<u>SPEC</u>	<u>RESULTS</u>
Penetration, Unworked	D 217	275 Min.	323
Penetration, Worked 60x	D 217	300 – 330	323
Penetration, Worked 5000x, Increase	D 217	+25 Max.	+10
Penetration, after 24hrs @ -30 C	D 217	100 Min.	189
Penetration, after 1 hr @ 120 C	D 217	380 Max.	377
Shell Roll Test, 4 hrs @ Room Temp.	D 217	+50 Max.	+23
Dropping Point, C	D 2265	204 Min.	315
Filler, Zinc Oxide, %	D 128	4.0 – 6.0	5.0

This grease is designed for use principally in applications that are not normally re-lubricated after the initial lubrication at the time of assembly. This grease exhibits excellent high and low temperature capabilities and is especially resistant to water spray and water washout.